

Prebona fogger – instructions

This instruction provides a short overview of how to use Prebona fogger to eliminate unwanted odors with Prebona OdorControl. Prebona fogger is a high quality cold fogger made by Wanjet AB (www.wanjet.se).

Before treating a space, such as a room or a car, make sure the space is clean and that source of odor is removed. Treatment with Prebona OdorControl will remove unwanted odors that is present in air and surfaces of an eclosed space. The odor elimination effect is almost immediate, i.e. odors are typicalle eliminated in minutes after treatment. Sometimes it is necessary to repeat treatment for best result. For more information on what odors are eliminated and expected effect, please visit www.prebona.com.

1. Open fogger and fill up Prebona OdorControl

Open fogger by removing motor and nozzle from tank. Fill tank with about 3 liter of Prebona OdorControl. Tilt steel pipe to the side when putting motor and nozzle back on the tank. Make sure motor and nozzle is aligned before closing metal ring.

2. Make sure air valve is open. Air valve is open when plastic tube is visible through ventialtion hole. If air valve is closed, a vacuum will build up in the tan, which will reduce output.

3. Adjust solution valve. The solution valve should be set at a low a numbe, e.g. between 1 and 2. A low setting provides a fine fogg with small droplets. Higher settings provide larger droplets and higher output. Small droplets provide better effect but increased treatment time. Be careful when adjusting solution valve as it is a plastic needle valve and sensitive to excessive force.

4. Connect to power. Use correct voltage (220V or 110V) and a cable long enough to carry out the job safely.

5. Put on protective gear. When using Prebona fogger with Prebona OdorControl, protective gear should be used. Use protective clothing, glasses, gloves, respiratory filter and ear plugs. Read safety data sheet before using Prebona OdorControl. Safety data sheet is available on www.prebona.com.

6. Direct the nozzle towards surface to be treated. The nozzle should be kept at a distance of 0,5 to 2 meters from the surface.

7. Flip the power switch to "on". It takes a few second for the liquid to reach the nozzle and fog to start.

8. Treatment. Start treatment at the back of the space to be treated and back out. Focus treatment on absorbing surfaces such as textile, wood and concrete. Treat under seats, beds and closets. Prebona OdorControl will leave a solid layer when let dry on a non-absorbing surface, such as glass and plastic. If Prebona OdorControl has been applied to unwanted surfaces, dry off with paper before product has dried. After use, clean nozzle with a soft cloth to avoid build-up of Prebona OdorControl.



Prebona fogger



Prebona fogger – open with steel pipe.



Air valve - open



Power switch



Solution valve



Eliminating odor in bathroom using Prebona fogger and Prebona OdorControl.